PRODUCT INFORMATION

4456 Adhesive Transfer Tape

Product Description:

4456 is a 40 microns clear, acrylic transfer tape coated onto an 80 gsm. yellow glassine paper release liner, reverse wound to be used in an ATG gun dispenser. It is recommended for all bonding, mounting and splicing applications.

Product Data:

	Unit	Nominal Value
Adhesive Film Thickness:	microns	40
Adhesive Liner Thickness:	microns	67
Peel Adhesion on Stainless Steel:	N/cm	2.8

Applications:

- Core starting of films, foils, paper webs.
- End tabbing of films, foils, papers.
- Mounting promotional cards
- Mounting albums, labels, leaflets, photo, posters, signs, stickers etc.
- Show card assembly
- Mounting sample cards.
- Point of sale assembly.
- Mounting display items.

Features & Benefits

- Excellent resistance to UV.
- Excellent temperature resistance.
- Long ageing performance.
- Reinforced with glass fibres for improved cohesive strength and clean break of adhesive.
- To be applied with **ATG** gun dispenser for improved efficiency.
- Service temperature: -30°C to +150°C (withstands shorter periods up to +180°C).

The information supplied is accurate to the best of Premier Tapes knowledge and is based upon all current available data. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and however arising. This document does not form any part of any contract with a customer.