



PRODUCT INFORMATION

PB0485 SBR Adhesive Tape

Product Description:

PB0485 is an unsupported adhesive supplied on a release paper in roll format. It is made from Styrene Butadiene Rubber (SBR) with a solvent free hot melt adhesive. It is amber in colour.

Product Data

	Unit	Nominal Value
Specific Gravity:	g/cm ³	0.98
Softening Point:	°C	85
Cohesion:	N/mm ²	0.6
Tack (Rolling Ball):	mm	30
Service Temperature Range:	°C	0 to 40
Application Temperature:	°C	10 to 20
Storage:	The adhesive is not UV resistant and should not be exposed to sunlight as degradation of the adhesive could occur.	

Applications:

- Lap-jointing of plastic sheet, damp proofing materials etc
- Joining/sealing of thin gauge aluminium skin in caravan/motorhome construction
- Bonding of roof skin to roof frame in commercial trailer manufacture
- Mounting of lightweight trim
- Fixing aid (third-hand fix)

Features & Benefits

- Provides a fast, clean and highly versatile method of forming a permanent and flexible bond between tow substrates without the need for priming, mixing or curing of liquid adhesives
- Will form a near-immediate bond to a wide range of substrates including metals, plastics and ceramic materials
- Release paper provides a finger lift along the adhesive edge
- Easy and clean to apply with minimal waste

The information supplied is accurate to the best of Premier Tapes knowledge and is based upon all current available data. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and however arising. Information in this document is provided for guidance only, and does not form any part of any contract with a customer.