



PRODUCT INFORMATION

5164

PVC Double Sided Foam Tape

Product Description:

5164 is a general-purpose, double-sided foam bonding tape. The product is white. The foam is predominantly closed celled. An acrylic pressure sensitive adhesive is coated on both sides, and the product has a paper release liner.

Product Data:

	Unit	Nominal Value
10 Minute 180° Peel Adhesion:	N/25mm	10
500 Hour Static Shear {stainless steel}:	Kg/cm ²	0.15
Dynamic Tensile Adhesion:	N/cm ²	45
Tensile Strength:	N/cm ²	118
Elongation at Break:	%	215
Thicknesses:	0.8; 1.5; 3.0; 4.5 mm	

Applications:

- For general mounting/bonding Forms a compression water seal
- For automotive mirror mounting For preventing electrolytic corrosion
- For glazing applications

Features & Benefits

- Maximum Recommended Weight Loading of 7 g/cm²
- Service temperature -40°C to +70°C
- Application temperature: +10C to + 40°C
- Shelf life of 1 year
- Minimum 20% compression required to effect a water seal
- Good resistance to dilute acids & alkalis
- Paper release liner, reducing dimensional change during application
- Very good Ultra Violet {UV} light resistance
- Resistance to abrasion, corrosion and moisture
- Suitable for indoor and outdoor environments
- No known hazards associated with this product
- Pre-determined dimensional sealant reduces waste

The information supplied is accurate to the best of Premier Tapes knowledge and is based upon all current available data. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and however arising. This document does not form any part of any contract with a customer.