



## PRODUCT INFORMATION

# 5474/5479

### PE Double Sided Foam Tape

#### Product Description:

5474 is a high performance double-sided foam bonding tape. The product is white. The polyethylene foam is predominantly closed celled. An aggressive rubber resin pressure sensitive adhesive is coated on both sides, and the product has a plain white paper release liner. The material can be supplied with a film liner facilitating automatic application. 5479 is available in black.

#### Product Data:

	Unit	Nominal Value
10 Minute 180° Peel Adhesion:	N/25mm	20
500 Hour Static Shear (stainless steel):	Kg/cm <sup>2</sup>	0.8
Dynamic Shear:	N/cm <sup>2</sup>	41
Thicknesses:		1.0,1.5,2.0mm

#### Applications:

- For general mounting/bonding
- For point of sale
- For mirror mounting

#### Features & Benefits

- Maximum Recommended Weight Loading of 36 g/cm<sup>2</sup>
- Service temperature -40°C to +70°C
- Application temperature: +10°C to + 40°C
- Shelf life of 1 year
- Minimum 20% compression required to effect a water seal
- Coated on both sides with a high quality pressure sensitive rubber resin adhesive
- Paper release liner, reducing dimensional change during application
- Resistance to abrasion, corrosion and moisture
- No known hazards associated with this product
- Pre-determined dimensional sealant reduces waste
- Clean to use
- Compatible with Lexan Polycarbonates
- Not recommended for UV exposure

The information supplied is accurate to the best of Premier Tapes knowledge and is based upon all current available data. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and however arising. This document does not form any part of any contract with a customer.