PRODUCT INFORMATION

PBBL310 Laminated Butyl Sealant Tape

Product Description:

PBBL310 is a waterproof, single sided butyl sealant tape with a foil laminate. It is available in black and white.

Product Data:

Composition:	Mono Element Butyl Latex
Heat Resistance:	90°C ± 2°C
Application Temperature:	-40°C to 90°C
Peel Adhesion (N/cm):	32 (600mm/min @ 23°C)
Elongation at Break (%):	400 (250mm/min @ 23°C)
Thickness and Colour:	1.0mm Black/White

Applications:

- Jointing membrane in roofing panels
- Sealing of joins in steel and timber framing
- Laminate helps prevent rubbing/wear in polyhouses

Features & Benefits

- Excellent resistance to UV light
- Useful life of 20+ years
- Good aging characteristics – does not crack or change colour
- Easy and clean to apply
- Non-toxic - environmentally friendly

The information supplied is accurate to the best of Premier Tapes knowledge and is based upon all current available data. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and however arising. This document does not form any part of any contract with a customer.