



PRODUCT INFORMATION

PF526-Reinforced Aluminium Foil Tape

Product Description:

PF526 is an aluminium foil-glass cloth backing (18u foil with an 8x8 mesh 95gsm glass cloth) with aggressive flame-retardant acrylic adhesive and protected by easy release liner.

Product Data:

	Unit	Value
Total Thickness (exclusive of liner):	Micron	180
Peel Adhesion:	N/25mm	18
Tack Rolling Ball:	cm	20
Tensile Strength:	N/25mm	250
Elongation:	%	5.0
Fire Rating:	(25/50 & Class O)	Passed
Service Temperature:	°C	-30 ~ +120
Applying Temperature:	°C	+10 ~ +40

Applications:

- Industrial Equipment and Pipes
- Vessel Engine Room's thermal insulation
- Used for HVAC

Features and Benefits:

- High Tensile & Tear Strength
- Match Foil-Glass Cloth Laminate
- UL 723 Approval and permanent bonding
- Outstanding Temperature and aging resistance

How to Apply:

- Remove any dust and grease from the surface.
- Separate the release liner from the tape and apply the tape along chosen surface.
- For a perfect seal, fully press the tape onto the surface and do not allow any air bubbles to form under the tape. Use a roller if required.
- If unable to remove dust and grease completely from the surface, a primer may be required to assist with adhesion. Wait until the primer is no longer sticky to touch before applying the tape.

The information supplied is accurate to the best of Premier Tapes knowledge and is based upon all current available data. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and however arising. This document does not form any part of any contract with a customer.



The information supplied is accurate to the best of Premier Tapes knowledge and is based upon all current available data. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and however arising. This document does not form any part of any contract with a customer.

www.premiertapes.co.nz