

PRODUCT INFORMATION

PF527 Paper Backed Foil Tape

Product Description:

PF527 is a foil tape with a 65u Foil-Kraft backing, combined with a transparent high performance solvent acrylic adhesive, protected by an easy-release silicone release paper.

Product Data:

	Unit	Nominal Value
Backing Thickness:	Microns	65
Total Thickness:	Microns	110
Peel Adhesion:	N/25mm	20
Tensile Strength:	N/25mm	85
Elongation at Break:	%	3.0
Service Temperature:	°C	- 30 to + 80
Application Temperature:	°C	+ 10 to + 40

Applications:

- Ideal within the HVAC industry for joining and sealing foil-scrim laminated fibreglass blanket, duct board joints and seams
- For joining and sealing flexible air duct seams and connections
- Also suitable for general industrial applications

Features & Benefits

- Excellent reflection of both heat and light
- Reliable and durable sealing in HVAC ductwork applications
- Low moisture vapour transmission rate
- Service temperature range from -30°C to + 80°C

Note: The product should be stored at room temperature and kept away from heat sources.
Shelf life – One year from shipment date when stored at 21°C and at 50% relative humidity and out of direct sunlight.

It is essential, as with all pressure sensitive tapes, that the surface to which the tape is applied is clean, dry and free of grease and oil.

The information supplied is accurate to the best of Premier Tapes knowledge and is based upon all current available data. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and however arising. Information in this document is provided for guidance only, and does not form any part of any contract with a customer.