



## PRODUCT INFORMATION

### 4029

## Double Sided PE Foam Tape

#### Product Description:

**4029** is a polyethylene foam tape coated both sides with a solvent based acrylic adhesive, giving good initial tack and long term bonding properties. The foam is black in colour with a yellow paper liner.

#### Product Data:

	Unit	Nominal Value
Loop Tack:	1kg/25mm	4.0
Peel Adhesion:	1kg/25mm	1.6
Shear Strength:	24hrs with 1.0kg/25mm x 25mm bonding stainless steel @ 25°C	
Heat Resistance:	24hrs with 0.5kg/25mm x 25mm bonding stainless steel @ 80°C	
Service Temperature Range:	•C	-20 to 90
Thickness:	mm	1.0

#### Applications:

- Bonding of emblems, mirror tiles, signs and plastic parts (indoor/outdoor)
- Fixing for plastic profiles and trim

#### Features & Benefits

- Flexible PE foam tape ideal for sealing against water, dust and light
- Secure bonding with good initial tack
- Good resistance to solvents, chemicals, UV and heat

The information supplied is accurate to the best of Premier Tapes knowledge and is based upon all current available data. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and however arising. Information in this document is provided for guidance only, and does not form any part of any contract with a customer.