



PF1300-Bi Directional Filament Tape



Product Description:

Bi Directional OPP/Fibre Glass Mesh Filament Tape

Product Data:

| | |
|-------------------------------------|-----------------------|
| Adhesive Type: | Hot Melt Rubber |
| Backing Liner: | OPP/Fibre Glass Mesh |
| Total Thickness (mm): | 0.140mm (140 microns) |
| Adhesion To Stainless Steel N/25mm: | 25 |
| Maximum Tensile N/25mm: | 550 |
| Temperature Resistance °C: | 60 |
| Elongation at break %: | 6 |

Applications:

- Bundling
- Strapping
- Packaging

The information supplied is accurate to the best of Premier Tapes knowledge and is based upon all current available data. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and however arising. This document does not form any part of any contract with a customer.



Features & Benefits

- Low Stretch
- Strong
- High adhesion to most surfaces
- Easy handling
- Good resistance to breakage

Conditions of Use:

- For best results apply between 15°C and 25°C in a dry environment.
- Application surfaces must be dry and free from dust and particles.
- Do not apply on surfaces treated or contaminated by anti-adhesives.
- Do not use paint containing additives which could reduce the adhesive properties.
- Avoid contact with surfaces containing plasticizers or other chemical agents not compatible with the tape.
- In cases of rough or irregular surfaces, it is better to use a tape with a higher quantity of adhesive.
- Care must be taken with reference to removability without residue and working conditions of the self-adhesive tape.

Tape Storage:

- Ideally store tape between 15°C and 25°C with a maximum relative humidity of 65%.
- Always store away from heat sources, avoiding exposure to light and if possible keep in the original packaging.
- When temperatures are lower than 15°C it is highly recommended to recondition the adhesive tape to normal temperatures (15°C to 25°C) before use.
- Self-adhesive tape technical features are generally not permanent but remain at their best for approximately twelve months, if stored according to suggested conditions and by avoiding extreme environmental conditions such as quick and sudden temperature changes, exposure to UV light and high levels of humidity.

The information supplied is accurate to the best of Premier Tapes knowledge and is based upon all current available data. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and however arising. This document does not form any part of any contract with a customer.