



## PRODUCT INFORMATION

### PS1433

### All Weather Tape

#### Product Description:

PS1433 is a polyethylene film tape coated one side with an acrylic adhesive, giving good weathering characteristics.

#### Product Data:

|                      | Unit    | Nominal Value |
|----------------------|---------|---------------|
| Tack:                | N/cm    | 3.0           |
| Holding Power:       | mins    | 1440          |
| Peel Adhesion:       | kg/in   | 1.40          |
| Tensile Strength:    | kg/in   | 4.50          |
| Elongation at Break: | %       | 300           |
| Film Thickness:      | microns | 80            |
| Total Thickness:     | mm      | 0.130         |

#### Applications:

- Temporary repair to polythene and other plastics used in poly houses
- General bundling and wrapping in outdoor applications

#### Features & Benefits

- Good resistance to UV
- A cost effective method of repairing rips and tears
- Clear colour blends well with background film
- Clean, easy and quick to apply

The information supplied is accurate to the best of Premier Tapes knowledge and is based upon all current available data. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and however arising. This document does not form any part of any contract with a customer.