



## PRODUCT INFORMATION

### PT238Gum - Reinforced Gum Paper Tape

#### Product Description:

PT238 is a Kraft paper taper coated one side with a vegetable glue adhesive.

#### Product Data:

	Unit	Nominal Value
Total Weight:	Grams	127 ±5
Initial Tack:	N/cm	5
Peel Strength:	N/25mm	3.1 @ 180°
Tensile Strength:	N/50mm	292 TD
	N/50mm	523 MD

#### Applications:

- Carton sealing
- Paper Splicing

#### Features & Benefits

- Clean and easy to apply in roll form

#### Application Requirements:

- Temperature between 0°C and +35°C.
- Surface must be clean and free from dust and grease.
- Avoid touching the tapes exposed adhesive surface in order to keep full adhesive performance.
- Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level.
- The indicated level of performance will be reached after a bonding period of 24 Hours at 23°C

#### Storage and Shelf Life:

Clean and dry in a well ventilated area, preferably at a temperature between 10°C and 30°C. Stored under these conditions shelf life will be a minimum of 12 months.

The information supplied is accurate to the best of Premier Tapes knowledge and is based upon all current available data. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and however arising. This document does not form any part of any contract with a customer.