



PRODUCT INFORMATION

4208

DOUBLE SIDED PE FOAM TAPE

Product Description:

4208 has an acrylic-solvent based pressure sensitive adhesive with high shear strength for secure bonding performance. It's reinforced with black 6 PCF cross-linked polyethylene foam for stable long term outdoor applications. Highly resistant to weather, oxidation, UV and extreme weather temperature ranges. (UL Approved – File no. MH 19350)

Product Data:

	Unit	Nominal Value
Loop Tack:	1Kg/25mm	3.5
Peel Adhesion:	1Kg/25mm	1.6 ±
Shear Strength:	24hrs with 2.0kg/25mm x 25mm bonding stainless steel @ 25°C	
Heat Resistance:	24hrs with 0.5kg/25mm x 25mm bonding stainless steel @ 80°C	
Normal Tensile Strength:	Over 30 Kg/25mm x 25mm	
Thickness:	0.8mm	
Colour:	Black	

Applications:

- Its weather and age resistance, and ability to bond with both smooth and rough surfaces make this suitable for outdoor applications.
- Widely used for exterior side molding of cars, mounting of emblems, plastic strips, trims and for various substrates

Features & Benefits

- Flexible PE foam ideal for sealing against water, dust and light
- Excellent high tack adhesive ideal for bonding various substrates
- Service temperature: -20°C to 100°C
- UV resistant with good aging properties

Note: For best results, store this product at 22°C and 50% relative humidity in its own box and use within 2 years from date receipt.

The information supplied is accurate to the best of Premier Tapes knowledge and is based upon all current available data. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and however arising. This document does not form any part of any contract with a customer.