

PRODUCT INFORMATION

635 D/S Structural Glazing Spacer Tape

Product Description:

635 is a double sided high tack PVC glazing tape coated both sides with an acrylic adhesive. It is designed for use in structural spacer systems and has an open cell structure to allow the curing of structural silicones on all sides. It has fast recovery from compression. It is available in black only.

Product Data:

	Unit	Nominal Value
Shore Hardness:	"OO" Scale	55-75
Tear Strength:	Kg/cm	2 min
Density:	Kg/m ³	300
Tensile Strength:	N/cm ²	0.35 Mps
Elongation at Break:	%	150
Thermal Conductivity (k):	Wm ⁻¹ K ⁻¹	0.19 Service
Temperature:		-50°C to +60°C
Thicknesses:	3.0mm; 6.0mm; 8.0mm; 9.5mm	

Applications:

- For use as the spacer element between the insulated glass unit and the frame during structural glazing fabrication where the primary bond is silicone adhesive

Features & Benefits

- Compatible with structural silicone adhesives
- Low thermal conductivity
- Good resistance to most chemicals, solvents and dilute acids
- Excellent ageing resistance
- Quick, clean and convenient to use
- No wastage
- Available in a range of thickness and widths

Note: 635 has been approved for compatibility with structural silicones by the major manufactures, Dow, Sika and GE.

The information supplied is accurate to the best of Premier Tapes knowledge and is based upon all current available data. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and however arising. This document does not form any part of any contract with a customer.